

Prostock mower rules

1. Must have a cage all the way around legs and back must be at least 2 inches above the seat. Cage can not be thicker than 1/4 in the cage must also be at least 3 in behind the motor
2. Allowed a front bumper MAX 28 inches in width, also allowed 16 inches of bumper shock welded to the frame, with up to 5 inches of shock past the front of the frame.
3. Bumper shocks are not allowed to connect to the front cage.
4. 3. Two 3/4 -1 inch all threads can be run in front of the motor with a 14x14 plate in front of the all thread welded to frame only.
5. Can have 2 kickers under hood attached to back of motor plate protector. Can run kicker to front foot pegs only.
6. Allowed to have a front and rear belly bar.
7. Can have metal floor pans.
8. Can have 4 3x3 1/4 gussets on each corner on frame to foot peg.
9. Hood must be bolted down and must be a factory hood, no homemade hoods
10. A 13x14 motor plate is allowed.
11. Allowed to reinforce factory steering components to the mower you built. No Aftermarket parts allowed.
12. Can run any rear end but must stay belt driven.
13. No larger than a 7 in pulley on front and no smaller than a 3 on pulley on the back
14. Can run aftermarket gas tank, shifter and gas pedal
15. Can run beadlock protectors on tires but can not be covered with cage
16. Motor must be under 25 hp it can be built but must start at 25hp block.
17. Must have a killswitch and a gas shut off that is accessible from the seat
18. You can lower your seat but must have factory fenders

19. Pointy bumpers are allowed but nothing over 6 inches from back of bumper, bumpers can not be no larger than 2x3 tubing
20. All hoods have to be cable of removing for inspection
21. Can have a battery , but must be secure and visible if not secured you will have to take it off.
22. No sharp edges everything must be rounded off
23. Back bumpers are allowed but nothing over 28 inches wide. Can have 16 in bumper shock welded to frame with 5 inches past back fenders
24. Rear bumper can not connect to cage or belly bars.
25. Posi rear ends are allowed
26. All mowers WILL be inspected and paid for before running
27. Restarts an roll over will be discussed at every event during driver meeting..